

ANALYTICAL SERVICES INCORPORATED

## BOA™ BREAKER OIL ANALYSIS OIL CIRCUIT BREAKER SAMPLE DATA

ACN 0968 16081

RETURN COMPLETED TO:  MAHANGA HOLDINGS LTD 24b WILLIAM PICKERING DRIVE ALBANY (PO BOX 40221 GLENFIELD) AUCKLAND PH 09 444 0663 FAX 09 444 1526		COMPAN ADDRESS	-	
P.O # (If applicable) Samp Syringe Number	led By:			
Sample Location (Substation/PHPP) Sample Date Equipment / Company Number Serial Number (Nameplate) Manufacturer (Nameplate) Date of Manufacture (Nameplate) Model Number / Type (Nameplate) Voltage Rating (Nameplate) Fluid Volume (Nameplate)  Pole (Tank) Phase Interrupting Rating (KA) (KVA) (MVA) Amp Rating (Nameplate) Present Counter Reading Oil Temperature Number of switching operations since last internal inspection	Ta OA	nk No. 1 OB OC	Tank No. 2 OA OB OC	Tank No. 3 OA OB OC
Present Accumulated Fault Count (ACC)  Date of last internal inspection  Date oil was last filtered  Date oil was last replaced  All Tests below are Required for BOA		%	Notes• The BO∆ d	iagnostic requires a one
Diagnostics Dissolved Gas Analysis(IEC-599) Particle Counts Moisture in Oil (IEC-814) Dielectric Breakdown (ASTMD-1816)		litre oil qual OCBs conta	lity sample and a DC aining more than 14	GA sample be taken. On litres of oil require rough the fill/drain valve

## PLEASE REMEMBER TO MARK 'BOA SAMPLE' ON SAMPLE CONTAINERS. THANK YOU.

Mahanga Holdings Ltd P O Box 40221 Glenfield 24b William Pickering Drive Albany, Auckland

Interfacial Tension (ISO-6295)

Acid Number (IEC-296)

Color (ISO-2049)

Urgent Inquiries - Ph 09 4440663 Fax 09 4441526

Mobile +64 21 464 103

**Reason for Test** 

- O Routine Test
- O Retest
- O This is a return to Service Test

prior to collecting samples. OCBs containing less than

1400 litres of oil require one litre of oil to be flushed

through the fill/drain valve prior to collecting samples.